





Mile Marker's all new Project ES (Element Sealed) winches feature best in class line speeds, corrosion proof construction, submersible solenoids with marine-grade connections, and have 19 watertight seals to conquer every element imaginable. Other winches claim "waterproof" or "sealed," but Mile Marker's Project ES winches were independently lab certified to the IP68 standard to be impermeable to liquid and dust. Mile Marker has a full line of the Project ES Winches ranging from 2500 pounds to 15,000 pounds....What's Your Element?

## SEC15(es) PERFORMANCE:

| LINE PULL |      | LINE SPEED |     | MOTOR CURRENT |
|-----------|------|------------|-----|---------------|
| lb        | kg.  | fpm        | mpm | amps @ 12 V   |
| 0         | 0    | 15.8       | 4.8 | 74            |
| 5000      | 2270 | 9.8        | 3   | 215           |
| 9000      | 4086 | 7.9        | 2.4 | 280           |
| 12000     | 5448 | 6.5        | 2   | 350           |
| 15000     | 6810 | 5.9        | 1.8 | 420           |
|           |      |            |     |               |

## SEC15(es) PRODUCT SPECIFICATIONS:

| Part Number        | 76-50260W   |  |  |
|--------------------|---|--|--|
| Rated line pull    | 15,000 lbs (6810 kgs), Single line                    |  |  |
| Gear Train         | 3 Stage Planetary                                     |  |  |
| Gear Ratio         | 296:1   |  |  |
| Motor              | Series Wound, 5.5 hp, 12 Volt,                        |  |  |
| Control Pendant    | Power-In, Power-Out Remote, 12' (3.7 m)               |  |  |
| Dimensions (LxWxH) | 22.44" X 6.29" X 11.00"<br>(570 mm X 160 mm X 280 mm) |  |  |
| Cable              | (Aircraft Cable) 10mm X 79"<br>(10 mm X 24 m)         |  |  |
| Drum Size:         | 2.9" X 8.9" (75 mm X 228 mm )                         |  |  |
| Net weight         | 101 lbs (46 kg)                                       |  |  |
| Bolt Pattern       | 4 Bolt Pattern, 10" x4.5"<br>(254 mm X 114.3 mm)      |  |  |

## **PRODUCT FEATURES:**

- Fully Sealed Winches
- Fast Line Speeds
- Series Wound Motors
- Multi-Mount Solenoid
- Clockable Gear Housing
- Load Holding Brake
- Marine Grade Remote Control Connectors
- Corrosion-Free Construction
- Submersible, 500 Amp Solenoid



Dacromet<sup>®</sup> coated Roller Fairleads



Fully Sealed New Design



**Clockable Gear Housing** 



Marine Grade Connections



Multi-Mount Submersible Solenoid



Corrosive Proof Construction