



TOUGH SERIES

ATV/UTV WINCH
WITH SYNTHETIC ROPE

- INCLUDES SYNTHETIC ROPE
- 300 AMP RATED SOLENOID
- REDESIGNED BRAKE SYSTEM
- BOTH HANDHELD AND HANDLEBAR REMOTE INCLUDED!




PE3.5

WITH SYNTHETIC ROPE
3,500 LB Capacity
(1588 kg)

B

PE2.5

WITH SYNTHETIC ROPE
2,500 LB Capacity
(1134 kg)

Mile Marker's lineup of ATV and UTV winches have been totally redesigned and now boast top-of-the-line recovery speeds, a new braking system, and now feature Synthetic Rope as an option. These winches include both a handheld remote control, as well as a handlebar mounted remote control providing "power in" and "power out" functions. Mile Marker has also developed a new 300 amp rated solenoid giving maximum duty cycle to these bantam size power houses. 

PRODUCT FEATURES:

- Fast Line Speeds
- 50' of Synthetic Rope
- Aluminum Hawse Fairlead
- Redesigned Braking System
- All Metal Planetary Gearing
- Includes Both Handheld and Handlebar Controls
- 300 Amp Rated Solenoid
- Center Focused Drum
- Free Spooling



Power-In, Power-Out Remote Control



Mountable Handlebar Remote Control

PE 3.5 PRODUCT SPECIFICATIONS:

| | |
|--------------------|--|
| Part Number | 77-53112B |
| Rated line pull | 3500 lbs (1588 kg) Single Line |
| Gear Train | 3 Stage Planetary |
| Gear Ratio | 153:1 |
| Motor | Permanent Magnet, 2 hp (1.5kw), 12 V DC |
| Control Pendant | Illuminated Joystick Remote, 12' (3.7 m) |
| Dimensions (LxWxH) | 13.0" X 4.1" X 4.2" (330 mm X 105 mm X 108 mm) |
| Synthetic Rope | 3/16" X 50' (nominal 5440 lbs, 2468 kg) (4.8 mm X 45.2 m) |
| Drum Size: | 1.5" X 3.15" (38.1 mm X 80 mm) |
| Net weight | 25 lbs (11.3 kg) |
| Bolt Pattern | 4 Bolt Pattern, 4.88" X 3", (124 mm X 76.2 mm) |

PE 2.5 PRODUCT SPECIFICATIONS:

| | |
|--------------------|--|
| Part Number | 77-53105B |
| Rated line pull | 2500 lbs (1134 kg) Single Line |
| Gear Train | 3 Stage Planetary |
| Gear Ratio | 241:1 |
| Motor | Permanent Magnet, 2 hp (1.5kw), 12 VDC |
| Control Pendant | Illuminated Joystick Remote, 12' (3.7 m) |
| Dimensions (LxWxH) | 13.0" X 4.18" X 4.3" (330 mm X 106.2 mm X 109.2 mm) |
| Synthetic Rope | 3/16" X 50' (nominal 5540 lbs, 2468 kg) (4.8 mm X 15.2 m) |
| Drum Size: | 2" X 3.15" (50.8 mm X 80 mm) |
| Net weight | 24.2 lbs (11 kg) |
| Bolt Pattern | 4 Bolt Pattern, 4.88" X 3", (124 mm X 76.2 mm) |

PE 3.5 PERFORMANCE:

| LINE PULL | | LINE SPEED | | MOTOR CURRENT | |
|-----------|------|------------|-----|---------------|--|
| lb | kg | fpm | mpm | amps @ 12 V | |
| 0 | 0 | 19 | 5.8 | 43 | |
| 500 | 227 | 16.2 | 4.9 | 62 | |
| 1000 | 454 | 14.4 | 4.4 | 95 | |
| 1500 | 680 | 13 | 3.9 | 110 | |
| 2000 | 907 | 11.7 | 3.6 | 130 | |
| 2500 | 1134 | 10.8 | 3.3 | 140 | |
| 3000 | 1360 | 10.2 | 3.1 | 152 | |
| 3500 | 1588 | 9.8 | 2.9 | 160 | |

PE 2.5 PERFORMANCE:

| LINE PULL | | LINE SPEED | | MOTOR CURRENT | |
|-----------|------|------------|------|---------------|--|
| lb | kg | fpm | mpm | amps @ 12 V | |
| 0 | 0 | 24 | 7.3 | 41 | |
| 500 | 227 | 21.8 | 6.64 | 70 | |
| 1000 | 454 | 17.1 | 5.2 | 100 | |
| 2000 | 907 | 10.9 | 3.32 | 175 | |
| 2500 | 1134 | 7.5 | 2.28 | 212 | |