



Mile Marker's all new Project ES (Element Sealed) winches feature best in class line speeds, corrosion proof construction, submersible solenoids with marine-grade connections, and have 19 watertight seals to conquer every element imaginable. Other winches claim "waterproof" or "sealed," but Mile Marker's Project ES winches were independently lab certified to the IP68 standard to be impermeable to liquid and dust. Mile Marker has a full line of the Project ES Winches ranging from 2500 pounds to 15,000 pounds....What's Your Element?

PE3.5(es) PERFORMANCE:

LINE PULL		LINE SPEED		MOTOR CURRENT
lb	kg.	fpm	mpm	amps @ 12 V
0	0	19	5.8	43
500	227	16.2	4.9	62
1000	454	14.4	4.4	95
1500	680	13	3.9	110
2000	907	11.7	3.6	130
2500	1134	10.8	3.3	140
3000	1360	10.2	3.1	152
3500	1588	9.8	2.9	160

PE3.5(es) PRODUCT SPECIFICATIONS:

Part Numbers	77-50112BW (with Cable) 77-53112BW (with Rope)		
Rated line pull	3500 lbs (1588 kg) Single Line		
Gear Train	3 Stage Planetary		
Gear Ratio	153:1		
Motor	Permanent Magnet, 2 hp (1.5kw), 12 V DC		
Control Pendant	Power-In, Power-Out Remote, 12' (3.7 m)		
Dimensions (LxWxH)	13.0" X 4.1" X 4.2" (330 mm X 105 mmX 108 mm)		
Cable	7/32" X 50' (nominal 5,600 lbs, 2540 kg) (5.45 mm X 45.2 m)		
Rope *	3/16" X 50' (nominal 5440 lbs, 2468 kg) (4.8 mm X 45.2 m)		
Drum Size: Diameter/Length	1.5" X 3.15" (38.1 mm X 80 mm)		
Net weight	25 lbs (11.3 kg)		
Bolt Pattern	4 Bolt Pattern, 4.88" X 3", (124 mm X 76.2 mm)		

PRODUCT FEATURES:

- Fully Sealed Winches
- Fast Line Speeds
- Permanent Magnet Motors
- Load Holding Brake
- Marine Grade Remote Control Connectors
- Submersible, 300 Amp Solenoid
- All Metal Planetary Gearing
- Includes Both Handheld and Handlebar Controls
- Center Focused Drum
- Free Spooling
- Roller or Aluminum Hawse Fairlead



Cable or Synthetic Rope Options



Handlebar Remote



Submersible Solenoid & Remotes