

| Performance Data | | | | | | Fill Rates | |
|------------------|------|----|-----------------------------|------|----|-----------------|----------------|
| PSI | CFM | A | BAR | LPM | A | 2.5 Gallon Tank | Fill Rate |
| 0 | 2.54 | 24 | 0 | 72.0 | 24 | 0 To 200 PSI | 3 Min. 13 Sec. |
| 10 | 2.47 | 25 | 1.0 | 69.0 | 26 | 165 To 200 PSI | 53 Sec. |
| 20 | 2.40 | 27 | 2.0 | 65.5 | 29 | 5.0 Gallon Tank | Fill Rate |
| 30 | 2.31 | 29 | 3.0 | 62.0 | 30 | 0 To 200 PSI | 7 Min. 11 Sec. |
| 40 | 2.22 | 30 | 4.0 | 58.5 | 32 | 165 To 200 PSI | 2 Min. 06 Sec. |
| 50 | 2.14 | 13 | 5.0 | 55.5 | 33 | | |
| 60 | 2.05 | 32 | 6.0 | 52.5 | 34 | | |
| 70 | 1.98 | 33 | 7.0 | 50.0 | 35 | | |
| 80 | 1.91 | 34 | 8.0 | 47.0 | 35 | | |
| 90 | 1.84 | 34 | 9.0 | 44.0 | 35 | | |
| 100 | 1.77 | 35 | 10.0 | 41.0 | 35 | | |
| 110 | 1.70 | 35 | 11.0 | 37.0 | 34 | | |
| 120 | 1.62 | 35 | 12.0 | 34.0 | 34 | | |
| 130 | 1.55 | 35 | 13.0 | 31.0 | 33 | | |
| 140 | 1.48 | 35 | 14.0 | 28.5 | 32 | | |
| 150 | 1.41 | 35 | | | | | |
| 160 | 1.31 | 34 | | | | | |
| 170 | 1.24 | 34 | | | | | |
| 180 | 1.17 | 34 | | | | | |
| 190 | 1.09 | 33 | | | | | |
| 200 | 1.02 | 32 | *Supply Voltage: 13.8 Volts | | | | |